

Technical specification

Ventilation mode

IPPV, A/C, PCV, SIMV, SPONT/CPAP, PSV, SIGH, MANU

Ventilator parameter

Tidal volume (Vt)	0 ~ 2000 mL
Frequency (Freq)	1 min ~ 100 min
Oxygen concentration	21 % ~ 100 %
I:E	4 : 1 ~ 1 : 8
PEEP	0 cmH ₂ O ~ 40 cmH ₂ O
Pressure limit	20 cmH ₂ O ~ 100 cmH ₂ O
Pressure triggering sensitivity (Ptr)	-20 cmH ₂ O ~ 0 cmH ₂ O (Based on PEEP)
Flow triggering sensitivity (Ftr)	0.5 cmH ₂ O ~ 30 cmH ₂ O
SIGH	0 (off) 1/100 ~ 5/100
Apnea ventilation	OFF, 5 s ~ 60 s

Monitoring parameter

Frequency (Freq)	0/min ~ 100/min
Tidal volume (Vt)	0 mL ~ 2500 mL
MV	0 L/min ~ 99 L/min
Airway pressure	0 cmH ₂ O ~ 100 cmH ₂ O
Dynamic lung compliance monitoring	1 mL/cmH ₂ O ~ 1000 mL/cmH ₂ O
Oxygen concentration	15 % ~ 100 %

Packing size

Main engine: L 560 * W 560 * H 605 mm
 G.W. : 35 KG, N.W. : 17 KG
 Air compressor: L 683* W 687 * H 1140 mm
 G.W. : 100 KG, N.W. : 65 KG

Alarm and protection

The AC power failure alarm	Power failure or no connection
Internal backup battery low voltage alarm	$\leq 11.3 \pm 0.3$ V
No tidal volume	No tidal volume within 6 s
High minute volume alarm	5 L/min ~ 99 L/min
Low minute volume alarm	1 L/min ~ 30 L/min
High airway pressure alarm	20 cmH ₂ O ~ 100 cmH ₂ O
Low airway pressure alarm	0 cmH ₂ O ~ 20 cmH ₂ O
High oxygen concentration alarm	19 % ~ 100 %
Low oxygen concentration alarm	18 % ~ 99 %
Continuous pressure alarm	(PEEP + 1.5 cmH ₂ O) over 16s
Suffocation warning	5 ~ 60 s
Fan error	Show on screen
Oxygen deficit	Show on screen
The maximum limited pressure	< 12.5 kPa

Working condition

Gas source	O ₂ , Air
Pressure	280 kPa - 600 kPa
Voltage	220 V \pm 22 V
Power frequency	50 Hz \pm 1 Hz
Input power	900 VA(With air compressor) 250 VA(Without air compressor)

Oscillogram

P-T(Pressure-Time)
 F-T(Flow-Time)
 P-V Loop(Pressure-Volume Loop)

Other models for your reference:



S1100B



S1100A



S1600

The picture is for reference only. For more information, please contact Superstar Medical sales representatives.

SUPERSTAR
 NANJING SUPERSTAR MEDICAL EQUIPMENT Co., Ltd.

Nanjing Superstar Medical Equipment Co., Ltd.

Address: No.6 Building, No.9 Bofu Road, Yanjiang Industrial Development Zone, Liuhe District, 211505 Nanjing, P. R. China.

Tel: +86-25-69971838 Mobile: +86-13813361534 Fax: +86-25-69658833

Email: Ricky005@superstar-med.com Web: <http://www.superstar-med.net>

Cherish your life, Cherish your health!

SUPERSTAR
 NANJING SUPERSTAR MEDICAL EQUIPMENT Co., Ltd.

S1100 ICU Ventilator

ADULT · PEDIATRIC

Friendly Powerful Reliable





S1100 ICU Ventilator

Application

The ventilator makes a good performance in operation room, ICU department and emergency treatment. It used to assist or replace the spontaneous breathing for adult pediatric and neonatal more than 2kg. 25 years experience in Market-oriented ventilator make us professional and reliable, satisfying all your needs in ventilation. Due to the flexible configuration, good quality and competitive price, S1100 has soon become the superstar of market

Feature

- 12.1" TFT screen displays the ventilation parameters, alarm information, and oscillograms, make every operation more easily.
- Multiple ventilation mode can meet different clinical requirements.(IPPV, A/C, PCV, SIMV, PSV, SPONT/CPAP, SIGH, MANUAL)
- 3 oscillograms for your choice, 2 of them can be displayed on the screen at the same time.
- Humidifier can heat and wet breathing gas, makes it comfortable for patient to breathe.
- Rapid oxygen supply, automatically offer high flow rate oxygen within two minutes
- High temperature resistance breathing circuit is reusable and anti-pollution.

Safety

- 14 types of sound and visual alarm information, easier for users to do some error checking and troubleshooting.
- Built-in oxygen concentration sensor, ensure stable precision of oxygen concentration.
- Easy to move with four casters, easy to stop with two brakes.
- Separate design of electronic circuit and gas flow rate keep safe running of ventilator.
- Compact long life internal battery can provide emergency power, avoid risk of patient.
- Self-check before operation, eliminate system mistake.

14 types of alarm and protection function

12.1" TFT LCD screen display, screen saver mode

Parameters monitoring

fast oxygen supply

Parameters setting

2 of 3 oscillograms can be displayed on the screen at the same time

Nebulization function

Oxygen concentration sensor

Humidifier
Heating and wetting, real-time temperature display

Display continuous working hours for the air compressor